

PREMIA DIESEL XTRA

PREMIA DIESEL SERIES designed to meet heavy duty high speed diesel engine lubrication requirements calling for following standard lubrication CI-4/CH-4/CF-4/; MB 228.3; MAN 3275; ACEA A3/B4-04; VOLVO VDS-2; MTU Level 2; CUMMINS CES 20076/77; MACK EO-M Plus.

PREMIA DIESEL SERIES offer exceptional deposit control, thermal oxidation characteristic and foaming stability to longer drain interval. Modern viscosity enhances oil workability on engine start-up and during operational temperature for optimum all conditions engine protection.

PREMIA DIESEL SERIES are recommended for top-tier latest model high speed diesel engine both on-road and heavy duty off-road application. *PREMIA DIESEL SERIES* also applicable for gasoline engine lubrication requiring API SL/SJ lubrication standard.

PREMIA DIESEL SERIES TECHNICAL SPECIFICATION

CHARACTERISTIC	TYPICAL VALUE	
	HDO	HDO XTRA
SAE Multi-Grade	15W-40	10W-40
Standard Performance	API CH-4/SJ	API CI-4/SL
Kin Viscosity @ 40°C	117.4	108.2
Kin Viscosity @ 100 °C	14.8	14.3
Viscosity Index	130	135
Flash Point, °C	235	240
Pour Point, °C	-28	-33
Total Base Number	11.5	11.5

