

PREMIA GX SERIES

PREMIA GX SERIES are premium grade multi-vehicle synthetic blend gasoline engine oil; design to meet the latest engineering specification calling for American API SN/CF standard and European ILSAC GF5-5.

PREMIA GX SERIES offers exceptional oxidation stability with combination of optimum detergency helps to maintain engine cleanness and prevent sludge build up for a better fuel consumption and longer drain interval.

PREMIA GX SERIES is best recommended modern gasoline powered engine with automatic fuel injection system for all year various types of driving conditions.

PREMIA GX SERIES TECHNICAL SPECIFICATION

CHARACTERISTIC	TYPICAL VALUE			
	GX SUPER	GX SPORTY	GX MAXI	GX RACING
Recommendation	5-10 years	0-5 years	0-5 years	Racing
Typical driving condition	Normal	City	All	Extreme
SAE Multi-Grade	10W-40	5W-30	5W-40	5W-50
Standard Performance	API SN	API SN/CF	API SN	API SN
Kin Viscosity @ 40°C	119.8	83.3	108.8	169.8
Kin Viscosity @ 100 °C	15.4	11.5	14.6	20.3
Viscosity Index	135	135	140	140
Flash Point, °C	240	240	245	245
Pour Point, °C	-30	-40	-40	-40
Total Base Number	9.3	9.3	9.3	9.3

